

Asphalt Sand

A key product for the construction industry, our Asphalt Sand is used in major roadworks and infrastructure projects across Melbourne.

Description

Asphalt Sand has a wide range of uses but as the name suggests is primarily used in asphalt production. Sourced at our Nyora quarry it is well suited for local conditions and used extensively in road construction projects across Melbourne.

A typical benefit of good quality asphalt sand is that it enhances the skid resistance of the road surface. It is also quite porous with good drainage and compacts well making it ideal for use as a base for paving stones and slab work.

For large scale projects MQG can custom blend asphalt sand to your specific requirements. Please contact us for more information.

Particle Size Range (% Passing)

Sieve mm	Minimum	Maximum
4.750	98	100
2.360	90	100
1.180	80	100
0.600	70	90
0.300	40	70
0.150	0	15
0.075	0	5
Unwashed PSD AS 1141.11.1		

Available From

Nyora Quarry

Bulk Density

1.5 – 1.7 t/m³

Typical Uses

- Production of asphalt

The above data is from internal and external testing and represents indicative results only which are not guaranteed. This product is screened through an 8mm mesh, material larger than 8mm may still be present. You must satisfy yourself that the product is suitable for the purpose for which you intend to use it. This product may contain organic material. Metro Quarry Group makes no representations as to suitability, fitness or merchantability. Metro Quarry Group does not guarantee specifications for any parameters e.g. Particle Size Distribution, Hydraulic Conductivity, pH, Clay & Fine Silts or Colour as sand is a natural & variable resource.