

# Regular Concrete Sand

A cost-effective washed sand produced to meet industry requirements for the manufacture of concrete, render and pavers.

## Description

MQG's Regular Concrete Sand is suited to a wide range of uses. These include concrete intended for kerbs, concrete slabs and driveways, and in concrete based products including pavers and tiles. It is also often used in the production of asphalt.

It is a well graded washed sand produced to meet industry requirements and a cost-effective option for concrete production throughout the State.

## Particle Size Range (% Passing)

Sieve mm	Minimum	Maximum
4.750	90	100
2.360	60	100
1.180	30	100
0.600	15	100
0.300	5	60
0.150	0	20
0.075	0	5
Unwashed PSD AS 1141.11.1		

## Available From

Nyora Quarry

## Bulk Density

1.5 – 1.7 t/m<sup>3</sup>

## Typical Uses

- Concrete and asphalt production
- Manufacture of tiles, pavers and other concrete products
- Kerbing and concrete slabs
- As a base for pavers and slabs

The above data is from internal and external testing and represents indicative results only which are not guaranteed. This product is screened through an 8mm mesh, material larger than 8mm may still be present. You must satisfy yourself that the product is suitable for the purpose for which you intend to use it. This product may contain organic material. Metro Quarry Group makes no representations as to suitability, fitness or merchantability. Metro Quarry Group does not guarantee specifications for any parameters e.g. Particle Size Distribution, Hydraulic Conductivity, pH, Clay & Fine Silts or Colour as sand is a natural & variable resource.